



Declaration of Performance

Kooltherm® K15

1000.CPR.2013.K15B.003

Unique identification code of the product-type:	Kooltherm® K15 Black
Intended use/es:	Thermal insulation for buildings
Manufacturer:	Kingspan Insulation Ltd, Herefordshire HR6 9LA,UK
System/s of AVCP:	System 3
Harmonised technical specification	BS-EN 13166:2012+A2:2016
Notified body/ies:	University of Salford NB 1145.B.I.T.S NB 1334.Exova NB 1104

Essential characteristics		Performance																										
Thermal resistance	Thermal resistance R_D ((m ² .K)/W)	<table border="0"> <tr><td>d_N 25mm</td><td>1.15</td></tr> <tr><td>d_N 30mm</td><td>1.40</td></tr> <tr><td>d_N 40mm</td><td>1.90</td></tr> <tr><td>d_N 50mm</td><td>2.50</td></tr> <tr><td>d_N 60mm</td><td>3.00</td></tr> <tr><td>d_N 70mm</td><td>3.50</td></tr> <tr><td>d_N 80mm</td><td>4.00</td></tr> <tr><td>d_N 90mm</td><td>4.50</td></tr> <tr><td>d_N 100mm</td><td>5.00</td></tr> <tr><td>d_N 120mm</td><td>6.00</td></tr> <tr><td>d_N 130mm</td><td>6.50</td></tr> <tr><td>d_N 140mm</td><td>7.00</td></tr> <tr><td>d_N 150mm</td><td>7.50</td></tr> </table>	d_N 25mm	1.15	d_N 30mm	1.40	d_N 40mm	1.90	d_N 50mm	2.50	d_N 60mm	3.00	d_N 70mm	3.50	d_N 80mm	4.00	d_N 90mm	4.50	d_N 100mm	5.00	d_N 120mm	6.00	d_N 130mm	6.50	d_N 140mm	7.00	d_N 150mm	7.50
	d_N 25mm	1.15																										
	d_N 30mm	1.40																										
d_N 40mm	1.90																											
d_N 50mm	2.50																											
d_N 60mm	3.00																											
d_N 70mm	3.50																											
d_N 80mm	4.00																											
d_N 90mm	4.50																											
d_N 100mm	5.00																											
d_N 120mm	6.00																											
d_N 130mm	6.50																											
d_N 140mm	7.00																											
d_N 150mm	7.50																											
Thermal conductivity λ_D (W/(m.K))	<table border="0"> <tr><td>d_N 25-44mm</td><td>0.021</td></tr> <tr><td>d_N 45-150mm</td><td>0.020</td></tr> </table>	d_N 25-44mm	0.021	d_N 45-150mm	0.020																							
d_N 25-44mm	0.021																											
d_N 45-150mm	0.020																											
Thickness tolerance	d_N 20-200mm T1																											
Reaction to fire	Reaction to fire	RtF C-s1,d0																										
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability Characteristics	NPD																										
Durability of thermal resistance against heat, weathering, ageing/ degradation	Durability Characteristics	NPD																										
	Dimensional stability under specified temperature and humidity condition	DS(70,90)																										
		DS(-20,-)																										
	Thermal conductivity λ_D (W/(m.K))	<table border="0"> <tr><td>d_N 25-44mm</td><td>0.021</td></tr> <tr><td>d_N 45-150mm</td><td>0.020</td></tr> </table>	d_N 25-44mm	0.021	d_N 45-150mm	0.020																						
d_N 25-44mm	0.021																											
d_N 45-150mm	0.020																											
Determination of the aged values of thermal resistance and thermal conductivity	RD and λ_D																											
Compressive strength	Compressive stress or compressive strength	CS(Y)100																										
Tensile / Flexural strength	Tensile strength perpendicular to faces	NPD																										
Durability of compressive strength against ageing / degradation	Compressive creep	NPD																										

Declaration of Performance

Water permeability	Short term water absorption	NPD
	Long term water absorption	NPD
	Closed cell content	CV
Water vapour permeability	Water vapour transmission	NPD
	Closed cell content	CV
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD
NPD: No Performance Determined		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



.....
Ralph Mannion
Managing Director UK and Ireland
Pembridge, England, UK
Version 3
Version date 1/1/2019
First signed 1/1/2019