



QuadCore[®]

PRODUCT SAFETY INFORMATION

These products are exempt from the requirements of Article 57 and 59(1) of REACH Regulation (EC) No 1907/2006. The information below follows the SDS format as described in Annex 2 of the Regulation.

1 Identification of Products and Company

Product

Kingspan QuadCore[®] 426 Roofboard

Company Identification

Company Name: Kingspan Insulation Limited
Company Address: Pembridge, Leominster, Herefordshire HR6 9LA, UK
Tel: +44 (0) 1544 388 601
Fax: +44 (0) 1544 388 888
Email: info@kingspaninsulation.com
Website: www.kingspaninsulation.com

2 Hazards Identification

Not applicable

3 Composition

Core: Rigid neo-thermoset (PUR or PIR as defined by EN 13165) insulation.

Alternative Facings: Composite foil.

4 First Aid Measures

Inhalation: Dust is non-hazardous.
Remove the person to fresh air.

Skin: Non-sensitising.
When facings containing glass fibres are handled, skin irritation may occur. Wash carefully using soap and water or a proprietary cleanser to remove.

Eyes: Dust particles should be removed by flushing with clean water.

Ingestion: No information available.

Other: Seek medical attention if discomfort persists.

5 Fire Fighting Measures

It is prudent to take precaution against ignition, fire spread and smoke hazard.

Suitable media: Waterspray (fog), foam, CO₂ or dry chemical.

Unsuitable media: N/A

Firefighters should use self-contained breathing apparatus and saturate burning foam with water from a spray nozzle. Dust is classified as weakly explosive (St. Class 1).

6 Accidental Release Measures

N/A

7 Handling and Storage

Store in original packaging in a location free from any ignition hazard such as open flames, cutting and welding torches, high surface temperature electric heaters and other forms of direct radiant heat.

Keep product protected from the elements. Ensure stability of stack and provide adequate aisle space for access between stacks.

8 Exposure Controls / Personal Protection

Inhalation:	Dust is non-hazardous. Dust from timber facings may cause respiratory irritation. As with all cutting procedures it is recommended that a disposable dust mask is worn. Where dust is generated through mechanical cutting in confined spaces, it is recommended that extraction be used.
Hands:	It is recommended that gloves be worn when handling the products.
Eyes:	Eye protection is recommended during mechanical cutting. When installing a product with reflective foil facings in very bright or sunny weather it is advisable to wear UV protective sunglasses or goggles.
Skin:	Non-sensitising. It is recommended to wear gloves when handling the product. When installing a product with reflective foil facings in bright sunlight, it is advisable to consider skin protection from UV.
Other:	The products are non-load bearing. Access and works should not be carried out on unsupported boards.

9 Physical and Chemical Properties

• Appearance:	Grey foam with reinforced foil complex.
• Odour:	Negligible.
• pH:	Neutral under normal conditions.
• Melting Point:	N/A
• Flash Point:	N/A
• Insulation Density:	Typically 30-60 kg/m ³
• Solubility in Water:	Insoluble.
• Solubility in Organics:	Some liquids may cause swelling.
• Other Data:	None.

10 Stability and Reactivity

Stable and unreactive during normal use (see Section 7).

11 Toxicological Information

No information available at this time.

12 Ecological Information

The products are inert and stable in water and soil.

13 Disposal Considerations

Waste insulation is non-hazardous.

Product dust created in the installation process is regarded as nuisance dust only, because of its inert nature.

Observe usual safety precautions with polythene bags, wrapping and packaging.

Clean, undamaged product may be re-used. Insulation core waste is fully recyclable.

Waste product should be disposed of in accordance with the Waste Hierarchy – Reduce, Re-Use, Recycle.

14 Transport Information

Read this section in conjunction with Section 7.

Ensure security of load and where necessary sheeting / roping should be used.

It is recommended that mechanical lifting equipment is used when moving bulk quantities.

15 Regulatory Information

N/A

16 Other Information

The information contained here is offered in good faith and is based on our current knowledge. We thereby withhold the right to update and amend this document as necessary.

The information should not be taken as guarantee of specific performance and users should make their own assessment and make all applicable personnel aware accordingly.

The wearing of appropriate safety equipment is strongly recommended as a precaution and the products should only be used in their design application.

Users should visit the Kingspan Insulation website or contact the Kingspan Insulation Technical Services Department to ensure information is current.



Kingspan Insulation Ltd
Pembridge, Leominster, Herefordshire HR6 9LA, UK
Tel: +44 (0) 1544 388 601 Fax: +44 (0) 1544 388 888
email: info@kingspaninsulation.co.uk
www.kingspaninsulation.co.uk