

Declaration of Performance

Inno-Torch tapered

1034_BI_2013_INNOTORCHT_002
 1001_BI_2013_INNOTORCHT_002

Unique identification code of the product-type: **Inno-Torch Tapered**
 Intended use/es: **Thermal insulation for buildings**
 Manufacturer: **EcoTherm Insulation (UK) Ltd, Harvey Road, Burnt Mills Ind Est, Basildon, Essex SS13 1QJ**
 System/s of AVCP: **System 3**
 Harmonised technical specification: **BS-EN 13165:2012+A1:2015**
 Notified body/ies: **FIW München NB. 0751 University of Salford NB 1145.Exova NB 1104**

Essential characteristics		Performance	
Thermal resistance	Thermal resistance R_D ((m ² .K)/W)	d_N 30mm	1.15
		d_N 40mm	1.50
		d_N 50mm	1.90
d_N 60mm		2.30	
d_N 70mm		2.65	
d_N 80mm		3.20	
d_N 90mm		3.60	
d_N 100mm		4.00	
d_N 120mm		5.00	
d_N 130mm		5.40	
d_N 140mm	5.83		
d_N 150mm	6.25		
d_N 200mm	8.33		
Thermal conductivity λ_D (W/(m.K))	$d_N < 80$ mm	0.026	
	d_N 80-119mm	0.025	
	$d_N \geq 120$ mm	0.024	
Thickness tolerance	d_N 25-200mm	T2	
Reaction to fire		NPD	
Durability of reaction to fire against heat, weathering, ageing / degradation		Reaction to fire does not change with time	
Dimensional stability under specified temperature and humidity condition		DS(70,90)3	
		DS(-20,-)1	
Deformation under specified compressive load and temperature conditions		DLT(2)5	
Compressive strength	Compressive stress or compressive strength	CS(10\Y)150	
Tensile / Flexural strength	Tensile strength perpendicular to faces	TR80	
Durability of compressive strength against ageing / degradation	Compressive creep	NPD	
Water permeability	Short term water absorption	NPD	
	Long term water absorption	NPD	
	Flatness after one sided wetting	NPD	
Water vapour permeability	Water vapour transmission	NPD	
Acoustic absorption index	Sound absorption	NPD	
Release of dangerous substances to the indoor environment		No harmonized test method available	
Continuous glowing combustion		No harmonized test method available	
NPD: No Performance Determined			

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Richard Burnley

Managing Director UK and Ireland 1/1/2016

Pembridge, England, UK, Selby, England, UK, Basildon, UK

