



TruckMaster®

PORTABLE DIESEL STORAGE AND DISPENSING



The Kingspan TruckMaster range has been specifically designed for the safe transportation of diesel fuel. This robust, portable solution offers users the ultimate convenience by allowing them to refuel remotely on-site.

Available from 200-430 litres. The TruckMaster is built from high quality polyethylene providing resistance to structural damage, changing weather conditions and UV radiation. It also offers a number of equipment options to suit all types of user.

Quality Design and Reliability

Offering a robust and resilient product design combined with a 5 year guarantee*, quality customer service and over 40 years' experience delivering high performing products worldwide - you know you can trust Kingspan.



Excellent Return On Investment

Lightweight, portable storage solution offering a faster and safer delivery of diesel to any point of use with model options which occupy only half a euro pallet** - saving you valuable time and money.



Portability

The TruckMaster is designed to go anywhere and to withstand toughest of site conditions offering liquid delivery a new mobility. The TruckMaster 430 litre features an internal baffle wall minimising the movement of liquid hence making the truck and the load more stable when in transit.



The 430 litre TruckMaster has been tested to meet the requirements of the European agreement (ADR) for the International Carriage of Dangerous Goods by Road***.

* With 1 year on equipment.

** The new TruckMaster 200 and 300 litres occupy only half a euro pallet.

*** TruckMaster 200 and 300 litres do not require ADR approval due to their smaller capacity.



TruckMaster®

SPECIFICATION SELECTOR

DESCRIPTION / CAPACITY	TM200 NEW SHAPE	TM300 NEW SHAPE	TM200	TM430
Level gauge				●
Ball valve on suction line				●
Suction line with mesh filter	●	●	●	●
12 V DC pump (max. flow rate 50 l/min)	●	●	●	●
6 m power cable with battery clamps	●	●	●	●
4 m flexible delivery hose			●	●
3,7 m flexible delivery hose	●	●		
Automatic nozzle	●	●	●	●
Lid with integrated lock			●	●
Lid with separate lock (lock not provided)	●	●		
Vacuum and pressure relief valve (VENT)	●	●	●	●
Lid with support gas struts				
4 lifting shackles			○	●
Battery powered LED lamp			○	●
24 V DC pump (max. flow rate 50 l/min)	○	○		○
12/24 DC pump (max. flow rate 70/35 l/min)				○
12 V DC pump (max. flow rate 85 l/min)				○
230 V AC pump (max. flow rate 56 l/min)				○
Digital flowmeter fixed to the nozzle	○	○	○	○
Digital flowmeter fixed to the pump				○

● Standard accessories ○ Optional accessories.

NEW TM 200



Capacity 200 litres
Length 600mm
Width 800mm
Height 620mm

NEW TM 300



Capacity 300 litres
Length 600mm
Width 800mm
Height 890mm

TM 200



Capacity 200 litres
Length 1180mm
Width 860mm
Height 500mm

TM 430



Capacity 430 litres
Length 1180mm
Width 860mm
Height 910mm



TruckMaster 300 L



TruckMaster 430 L

Equipment specification:

1. Tank
2. Pump
3. Automatic nozzle
4. Vent
5. Delivery hose
6. Lockable lid*
7. Shackles**
8. 4" Inspection lid**
9. Filling offset**

* Lid with integrated lock (TM200, TM430) TM200 & TM300 can be locked with the padlock (padlock not provided).

** Only available on certain models.